

## LA350 FINE FOCUS ASSEMBLY

The LA350 allows for fine focus adjustment of the lens to the material. When the barrel is rotated, it raises or lowers the lens by 0.100 inches per full turn. The fine pitch adjustment enables precise set-ups. A scale is marked on the tube to provide an exact reference of the location. The assembly accepts a wide variety of optics for various focal lengths. (1.1" diameter lens)

### LA350 FINE FOCUS ASSEMBLY SPECIFICATIONS:

- \*  $\pm .50$  inches (12.7mm) Focus Adjustment
- \* Focus Lens Options (4" standard)
- \* Nozzle Tip Options (4" standard)
- \* Anodized Aluminum, Stainless Steel & Brass Construction
- \* Mounting Thread, 2"-20 (adapters available)

ITEM#	DESCRIPTION	PART #
2	Body	ESL 65799
3	Plunger	ESL 66115
4	Barrel	G 112131
5	Lead Screw	ESL 64310
6	Retainer Ring	ESL 64294
7	Drive Pin	ESL 65405
8	Slug, Lead screw	ESL 65401
9	Lens Mount	ESL 64296
10	Retainer, Lens	ESL 64289-1
11	Nozzle 4" FL, std.	ESL 64311
15	Lens, 4" FL, std.	ESL 64510-3



